



by Honeywell

Technical Specifications

Miller H-Design 1pts Harness Mating buckles

Description:

Miller H-Design 1 point harness with mating buckles on chest and legs straps.

The Miller H-Design harnesses are the new generation of harnesses dedicated to construction and general industry sectors providing more comfort, freedom of movements and safety to workers.

References:

1032830	H-Design 1pt mating buckle size 0
1032831	H-Design 1pt mating buckle size 1
1032832	H-Design 1pt mating buckle size 2
1032833	H-Design 1pt mating buckle size 3



SIZE SELECTION GUIDE

WEIGHT											
140	ON REQUEST										
130											
120	ON REQUEST	SIZE 1				SIZE 2				SIZE 3	
110											
100	ON REQUEST	SIZE 1	SIZE 2				SIZE 3				ON REQUEST
90											
80	ON REQUEST	SIZE 1	SIZE 2				SIZE 3				ON REQUEST
70											
60	ON REQUEST	SIZE 1	SIZE 2				SIZE 3				ON REQUEST
50											
40	ON REQUEST	SIZE 1	SIZE 2				SIZE 3				ON REQUEST
	150	155	160	165	170	175	180	185	190	195	200
HEIGHT											

Images are for guidance only.

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com

Benefits:

COMFORT AND FREEDOM OF MOVEMENTS

- o Exclusive H architecture of the harness, thanks to its ergonomically placed webbing, providing a total freedom of movements for the arms.
- o Horizontal leg straps preventing uncomfortable friction on the legs and on the groin (vs traditional leg straps) increasing comfort for the user during work.

EASY AND QUICK ADJUSTABILITY & CONNECTION

- o Easy to access and adjust buckles: intuitive movement up to down.
- o Very accessible anchor points: bended position back D-ring
- o Adjustable chest strap for a perfect fit in height and width.
- o Adjustable leg straps.
- o Easy Front strap clip.



GREATER SAFETY AND EASIER TRACEABILITY:

- o Fluor green textile, high visible stitching, back fall indicators to facilitate visual inspection before working.



**Fall indicators
on the back plate
for easy inspection**

- o Labels improving yearly checking follow-up for a better traceability
- o Water-repellent and stain free webbing for greater product durability.
- o Hi-visibility vest (option) to see workers even in dark environments (EN ISO 20471)

Features :

Shoulder Straps :

Standard green 44 mm webbing.
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Other Straps :

Standard black webbing 44 mm
PES with PTFE treatment (water repellent / anti stain)
Breaking strength : > 2700 daN

Back Anchorage D-ring :

Material : steel
Finish : Zinc plated Silver
Breaking strength : > 2300 daN

Steel mating buckles :

Finish : Zinc plated Silver
Breaking strength : > 900 daN

Weights :

Ref	Designation	Weight (kg)
1032830	H-Design 1pt mating buckle size 0	0,92
1032831	H-Design 1pt mating buckle size 1	0,94
1032832	H-Design 1pt mating buckle size 2	0,96
1032833	H-Design 1pt mating buckle size 3	0,98

Breaking strength: > 15 KN
Temperature: -30°C to +50°C

EN 361 Full Body Harnesses

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com