



TEGERA® 9182

Anti-vibration glove, full grain goatskin of top quality, Vibrothan®, Cat. II, black, yellow, extra long, for heavy work

PROPERTIES

Very durable, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Anti-vibration gloves

CATEGORY Cat. II

SIZE RANGE (EU) 9, 10, 11

COLLECTION PRO

PALM MATERIAL Full grain goatskin of top quality, Vibrothan®

BACK MATERIAL Full grain goatskin of top quality

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

LENGTH RANGE 315-335 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/36

PIECES PER BOX 0

DISPLAY No thread OUTER MATERIAL SPECIFICATION
Leather, natural latex, polyurethane

1(3)

VIBROTHAN®

SIZE	ART. NO.	EAN NO.
9	9182-9	7392626059399
10	9182-10	7392626055933
11	9182-11	7392626055940

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9182

FEATURES

Vibration-reducing according to EN ISO 10819, extra long, padded palm

PREVENTS RISK OF

Vibration injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY INDUSTRIES OF USE


Mining, machinery and equipment, MRO, automotive, building and construction

TYPE OF WORK

Heavy weight

2(3)

 Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3111X EN ISO 10819:2013

EN ISO 11640:2012



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9182

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	


Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN ISO 10819:1997 Mechanical vibration and shock



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3111X EN ISO 10819:2013

EN ISO 11640:2012 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com