TEGERA®



MicroThan®+



SIZE	ART. NO.	EAN NO.
7	9123-7	7392626070073
8	9123-8	739262607478
9	9123-9	7392626070110
10	9123-10	7392626070035
11	9123-11	7392626070059
12	9123-12	7340118328539

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9123

Synthetic leather glove, unlined, 0,7 mm Microthan®+, diamond grip pattern, polyester, Cat. II, black, yellow, reinforced seams, chrome free, for touchscreen, elasticated 360°, for assembly work

PROPERTIES

Good fingertip sensitivity, flexible, durable, excellent grip, perfect fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

COLLECTION PRO

PALM MATERIAL Microthan®+

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Unlined

DEXTERITY 3

GRIP PATTERN Diamond grip pattern

FASTENING Elasticated 360°

LENGTH RANGE 200-235 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

2021-01-21 www.ejendals.com

TEGERA®



CE Cat. II

EN 420:2003 + A1:2009







TEGERA® 9123

FEATURES

For touchscreen, chrome free, high visibility colour, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, short model, ergonomically shaped, reflector, specially designed details

PREVENTS RISK OF

Chrome allergy, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

PRIMARY ENVIRONMENTS OF USE

Dark environments, slippery environments, dry environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Agricultural work, airport work, assembly, building and construction, carpentry, construction, engineering, fine assembly, forest work, gardening, HVAC installation, installation work, machine driving, machine operating, mining, paper industry work, soil preparation, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

TYPE OF WORK

Medium weight



EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com

> > www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA®

TEGERA® 9123

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

 $EN\,388{:}2016\,Protective\,gloves\,against\,mechanical\,risks$

Property	Level Achieved	(Maximum Performance)		
a) Resistance to abrasion (No. of revolutions)	1	(4)		
b) Cut resistance (Index)	1	(5)		
c) Tear resistance (N)	2	(4)		
d) Puncturing resistance (N)	1	(4)		
e) Cut resistance, EN ISO 13997 (N)	Х	(F)		
f) Impact protection, EN 13594:2015		(P)		

EN 388 - Testing

f) Impact protection, EN 13594:2015

(specifies the requirements that apply for each safety level).

Level of protection/Performance level		2	3		4	5
a) Resistance to abrasion (No. of revolutions)	100	500	200	00	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	0	10,0	20,0
c) Tear resistance (N)	10	25	50)	75	
d) Puncturing resistance (N)	20	60	100		150	
Level of protection/Performance level		В	С	D	Е	F

e) Cut resistance, EN	ISO 13997 (N)	2	5	10	15	22	30
Level of protection/Performance level				F	•		





EN 420:2003 + A1:2009







All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



Pass (Level 1 ≤ 9 kN)

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10