



TEGERA® 682A

Synthetic glove, latex, 3/4 dipped, sandy finish, 10 gg, acrylic, Cat. II, grey, orange, high visibility colour, water repellent palm and knuckle, for allround work

PROPERTIES

Durable, good grip, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING 3/4 dipped

DIPPING MATERIAL Latex

LINING MATERIAL 10 gg, Acrylic

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 240-280 mm

COLOUR Grey, Orange

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL

SPECIFICATION Natural latex, acrylic

SIZE	ART. NO.	EAN NO.
7	682A-7	7340118316475
8	682A-8	7340118316499
9	682A-9	7340118316512
10	682A-10	7340118316437
11	682A-11	7340118316451

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 682A

FEATURES

High visibility colour, water repellent palm and knuckle

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Cold environments, wet environments

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, concrete work, construction

PRIMARY INDUSTRIES OF USE




Agriculture, transportation, building and construction

TYPE OF WORK

Heavy weight

2(3)

CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 2232X  EN 511:2006 02X 

Contact heat valid for coated area only

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 682A

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003 + A1:2009



EN 388:2016 2232X



EN 511:2006 02X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.