



MicroThan®+



SIZE	ART. NO.	EAN NO.
8	9190-8	7392626030541
9	9190-9	7392626030558
10	9190-10	7392626030565
11	9190-11	7392626030572

TEGERA® 9190

Synthetic leather glove, winter-lined, 0,7 mm Microthan®+, diamond grip pattern, polyester, fleece, Cat. II, black, grey, yellow, wrist support, chrome free, hook-and-loop, for allround work

PROPERTIES

Flexible, excellent grip, perfect fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

COLLECTION PRO

PALM MATERIAL Microthan®+

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

FASTENING Hook-and-loop

LENGTH RANGE 255-280 mm

COLOUR Black, Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Acrylic

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9190

FEATURES

Wrist-supporting, extra long, chrome free, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, water repellent, moisture resistant, ergonomically shaped, reflector, specially designed details

PREVENTS RISK OF

Chrome allergy, wrist injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Dark environments, slippery environments, dry environments, cold environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Airport work, building and construction, carpentry, construction, engineering, installation work, machine driving, machine operating, mining, soil preparation, transport work, warehouse work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2222X



EN 511:2006
21X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9190

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2222X



EN 511:2006
21X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com